

50000 liter tank i Rostfritt 304



406,000,00 kr /st exkl moms

item available on order

Article type: brand new storage tank - type TZN-SL

Volumetric volume (L): 50.000 L

Max. density P (kg/m³): 1.000

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin



Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 13 °

Shape of tank: cylindrical

Bottom type: conical 20 °

Total discharge: yes

Fixation points: 6 non adjustable feet

Manway(s): RVS 304

Gasket manway(s): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Inspection of: No Documentation

Flange for agitator: no

Number of manways: 2

Position of manway: headside

Height manhole 1 (mm): 500 mm

Position 2nd manway: cylinder

Height manhole 2 (mm): 440 x 308 mm

Tank outlet: inside Ø 80 mm

Outlet type: DIN 11851

Top: 2,50 mm

Cylinder: 2,50 mm

Bottom: 4 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 2.984 mm

Cylinder height: 7.000 mm

Height of top: 382 mm

Height of bottom: 600 mm

Feet height: 1.000 mm

Total height of tank: 8.382 mm

Empty weight tank: 1.850

SKU: 5978

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Maximal densitet för produkten: 1000

Mobil tank: Nej

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 20 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 50000



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
med besiktning av: No Documentation
Tankutlopp: inside Ø 80 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN 11851

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 7.000 mm
Höjd på fötter: 1.000 mm
Mått utlopp till marken: 400 mm
Total höjd: 8.382 mm
Ytterdiameter: 2.984 mm

Tjocklek på tank

Botten: 4 mm
Cylinder: 2,50 mm
Topp: 2,50 mm

Mer

Isolerad: Nej
Vikt: 1.850