

## 50000 liter tank i Syrafast 316



**468,000,00 kr /st exkl moms**

item available on order

**Article type:** brand new storage tank - type TZN-SL

**Volumetric volume (L):** 50.000 L

**Max. density P (kg/m<sup>3</sup>):** 1.000

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 40 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical



**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Top type:** conical 15 °

**Shape of tank:** cylindrical

**Bottom type:** conical 20 °

**Total discharge:** yes

**Fixation points:** 6 non adjustable feet

**Manway(s):** RVS 316

**Gasket manway(s):** EPDM

**Valve:** RVS 316L

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 2

**Position of manway:** headside

**Height manhole 1 (mm):** 500 mm

**Hinged lid:** yes

**Position 2nd manway:** cylinder

**Height manhole 2 (mm):** 440 x 308 mm

**Hinged lid:** yes

**CIP spray ball:** no

**Tank outlet:** inside Ø 80 mm

**Outlet type:** DIN 11850

**Total outlet valve:** no, optional

**Agitator:** no

**Top:** 3 mm

**Cylinder:** 2,50 mm

**Bottom:** 4 mm



**Distance from outlet to ground:** 405 mm

**Outer diameter tank:** 3.000 mm

**Cylinder height:** 7.000 mm

**Height of top:** 443 mm

**Height of bottom:** 615 mm

**Feet height:** 945 mm

**Total height of tank:** 8.800 mm

**Empty weight tank:** 1.850

**SKU:** 5843

Mer information



## Beskrivning av produkt

Livsmedelsklassad: Ja  
Material: Syrafast 316  
Modell: Vertikal  
Nyttillverkad/Begagnad: Nyttillverkad  
Arbetstryck i tank: ATM – atmosfERIC  
Konfiguration: single-skin  
Max. arbetstemperatur: 40 °C  
Maximal densitet för produkten: 1000  
Mobil tank: Nej  
Omrörare: Nej  
Tankens form: cylindrical  
Total urtappning: Ja  
Typ av botten: conical 20 °  
Uppvärmning/kylning: Nej  
Vätskeberörd yta: SS AISI 316 (V4A)  
Volym i liter: 50000

## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Nej  
Livsmedelsklassad: Ja  
Tankutlopp: inside Ø 80 mm  
Teknisk ritning finns: Nej  
Utloppstyp: DIN 11850

## Översikt material

Material: Syrafast 316  
Fixeringspunkt(er): RVS 304



## **Dimensioner av tank**

Cylinderhöjd: 7.000 mm

Höjd på fötter: 945 mm

Mått utlopp till marken: 405 mm

Total höjd: 8.800 mm

Ytterdiameter: 3.000 mm

## **Tjocklek på tank**

Botten: 4 mm

Cylinder: 2,50 mm

Topp: 3 mm

## **Mer**

Isolerad: Nej

Vikt: 1.850