

50000 liter tank i Rostfritt 304



668,000,00 kr /st exkl moms

Additional information: Pictures show the smaller 31,000 liter version (15487) of the tank; heating jacket approx. 3,930 mm of the lower cylinder height; manhole approx. 430 x 540 mm; tank is currently suspended in a transport frame made of Fe; 1 loose ladder bracket is included in the scope of delivery (would have to be welded on by the customer if required)

Volumetric volume (L): 50.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 3 Bar

Max. working temperature: 80 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: yes

Position of manway: cylinder

Outlet of tank: DN80 DIN 11851

Top: 4 mm

Cylinder: 3 mm

Bottom: 5 mm

Internal diameter tank: 2.800 mm

Outer diameter tank: 3.000 mm

Cylinder height: 8.000 mm

Total height of tank: 9.900 mm

SKU: 483186

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Pictures show the smaller 31,000 liter version (15487) of the tank; heating jacket approx. 3,930 mm of the lower cylinder height; manhole approx. 430 x 540 mm; tank is currently suspended in a

Övrig information2: transport frame made of Fe; 1 loose ladder bracket is included in the scope of delivery (would have to be welded on by the customer if required)

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 50000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 8.000 mm

Invändig diameter: 2.800 mm

Total höjd: 9.900 mm

Ytterdiameter: 3.000 mm

Tjocklek på tank

Botten: 5 mm

Cylinder: 3 mm

Topp: 4 mm

Mer

Isolerad: Ja