50000 liter tank i Syrafast 316



302 000 SEK /st exkl moms

Additional information: Steel feet cut off below the mounting flange (see pictures); inside with reinforcement rings (see pictures)
Volumetric volume (L): 50.000 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN100
Internal diameter tank: 3.600 mm
Cylinder height: 4.050 mm

Total height of tank: 6.000 mm
Empty weight tank: 7.000

SKU: 567560

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Chemistry; Steel feet cut off below the mounting flange (see pictures); inside with reinforcement rings (see pictures)
Omrörare: Nej
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 50000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 4.050 mm
Invändig diameter: 3.600 mm
Total höjd: 6.000 mm

Mer
Isolerad: Nej
Vikt: 7.000