

507 liter tank i Syrafast 316



136 000 SEK /st exkl moms

Additional information: Vessel currently bolted to an aluminum frame

Volumetric volume (L): 507 L

Pressure in tank: ATM - atmosferic

Max. pressure (Bar): 6,60 Bar

Max. temperature (°C): 180 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 2 L

Max Overpressure: 6 Bar

Max. working temperature: 180 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 140

Power: 0,37

Top: 10 mm

Cylinder: 6 mm

Bottom: 6 mm

Internal diameter tank: 812 mm

Outer diameter tank: 1.026 mm

Cylinder height: 750 mm

Total height of tank: 3.100 mm

SKU: 566318

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 180 °C

Mobil tank: Nej

Övrig information: Vessel currently bolted to an aluminum frame; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6,60 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 507

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 750 mm
Invändig diameter: 812 mm
Total höjd: 3.100 mm
Ytterdiameter: 1.026 mm

Omrörare

Kraft (kW): 0,37
Varvtal: 140

Tjocklek på tank

Botten: 6 mm
Cylinder: 6 mm
Topp: 10 mm

Mer

Isolerad: Ja