507 liter tank i Syrafast 316



136 000 SEK /st exkl moms

Additional information: Vessel currently bolted to an aluminum frame
Volumetric volume (L): 507 L
Pressure in tank: pressure
Max. pressure (Bar): 6,60 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 6,60 Bar

Max. temperature (°C): 180 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 2 L
Max Overpressure: 6 Bar

Max. working temperature: 180 °C
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: headside
Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 140
Power: 0,37

Top: 10 mm
Cylinder: 6 mm
Bottom: 6 mm
Internal diameter tank: 812 mm
Outer diameter tank: 1.026 mm

Cylinder height: 750 mm
Total height of tank: 3.100 mm

SKU: 566318

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 180 °C
Mobil tank: Nej
Övrig information: Vessel currently bolted to an aluminum frame; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 6,60 Bar
Total urtappning: Ja
Undertryck (vakuum): 6,60 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 507

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 750 mm
Invändig diameter: 812 mm
Total höjd: 3.100 mm
Ytterdiameter: 1.026 mm

Omrörare
Kraft (kW): 0,37
Varvtal: 140

Tjocklek på tank
Botten: 6 mm
Cylinder: 6 mm
Topp: 10 mm

Mer
Isolerad: Ja