

510 liter tank i Syrafast 316



161 000 SEK /st exkl moms

Additional information: Pharmacy; Handhole diameter appr. 155 mm in the upper bottom

Volumetric volume (L): 510 L

Pressure in tank: pressure

Max. pressure (Bar): 3 Bar

Max. temperature (°C): 133 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 48 L

Max Overpressure: 2,50 Bar

Max. working temperature: 133 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN20 DIN 11851

Agitator: yes

Number of revolutions: 124 - 620

Power: 0,55

Internal diameter tank: 790 mm

Outer diameter tank: 950 mm

Cylinder height: 850 mm

Total height of tank: 2.400 mm

SKU: 278755

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 133 °C

Mobil tank: Nej

Övrig information: Pharmacy; Handhole diameter appr. 155 mm in the upper bottom; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 510

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 850 mm
Invändig diameter: 790 mm
Total höjd: 2.400 mm
Ytterdiameter: 950 mm

Omrörare

Kraft (kW): 0,55
Varvtal: 124 - 620

Mer

Isolerad: Ja