

5100 liter tank i Rostfritt 304



70,000,00 kr /st exkl moms

Additional information: Fruit juice industry; Attention: Contrary to the information on the nameplate, this tank cannot be heated/cooled; The tank was probably formerly equipped with a heating-coil inside (unlike the welded brackets, this is no longer present); Manhole diameter approx. 420 mm; Insulation is cut out in several places; small dents in the insulation jacket; The outlet pipe tapers towards the tank to an internal

pipe diameter of approx. 80 mm; some residues of previous content; Metallic discolouration inside

Volumetric volume (L): 5.100 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 75 L

Max Overpressure: 8 Bar

Max. working temperature: 169 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN100 DIN 11851

Internal diameter tank: 1.890 mm

Outer diameter tank: 2.000 mm

Total height of tank: 3.050 mm

SKU: 300416

Mer information
