

5100 liter tank i Rostfritt 304



69 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: The agitator drive is missing, there is a loose piece of the platform in the tank.

Volumetric volume (L): 5.100 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes



Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 3 non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Valve: RVS 304

Gasket shut-off valve (mat): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Tank outlet: inside Ø 50 mm

Outlet type: DIN11851

Total outlet valve: yes

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: riveted

Insulation thickness: 50

Internal diameter tank: 1.400 mm

Distance from outlet to ground: 200 mm

Outer diameter tank: 1.550 mm

Cylinder height: 3.340 mm

Total height of tank: 4.500 mm

Empty weight tank: 600

SKU: 489486

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: The agitator drive is missing, there is a loose piece of the platform in the tank.

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5100



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851
Utloppsventil: Ja

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 3.340 mm
Invändig diameter: 1.400 mm
Mått utlopp till marken: 200 mm
Total höjd: 4.500 mm
Ytterdiameter: 1.550 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: riveted
Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Isoleringstjocklek OW: 50
Isolerad: Ja
Vikt: 600

