

## 51000 liter tank i Rostfritt 304



**357,000,00 kr /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** we can't give any guarantees about the agitator

**Volumetric volume (L):** 51.000 L

**Ra inner weld:** 0,80

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no



**Insulation:** yes

**Mobile tank:** no

**Top type:** conical

**Shape of tank:** cylindrical

**Bottom type:** conical

**Total discharge:** yes

**Fixation points:** 6 non adjustable feet

**Insulation material:** Rockwool

**Outer jacket (ornamental wall):** RVS 304

**Manway(s):** RVS 304

**Gasket manway(s):** unknown

**Fixation point(s):** RVS 304

**Wet parts agitator(s):** SS AISI 304 (V2A)

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 2

**Position of manway:** at the top

**Height manhole 1 (mm):** 440 mm

**Hinged lid:** yes

**Position 2nd manway:** in the bottom

**Height manhole 2 (mm):** 440 x 305 mm

**Agitator:** yes

**Agitator type:** propeller agitator

**Power:** 7,50

**Current:** 13,70

**Insulation body:** yes

**Insulation thickness:** 60

**Internal diameter tank:** 2.900 mm

**Distance from outlet to ground:** 750 mm

**Outer diameter tank:** 3.050 mm

**Cylinder height:** 8.000 mm

**Empty weight tank:** 5.000

**SKU:** 192914

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 51000

## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Nej  
Livsmedelsklassad: Ja  
Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304  
Fixeringspunkt(er): RVS 304  
Isoleringsmaterial: Rockwool  
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)  
Ytterbeklädnad: RVS 304

## Dimensioner av tank

Cylinderhöjd: 8.000 mm  
Invändig diameter: 2.900 mm  
Mått utlopp till marken: 750 mm  
Ytterdiameter: 3.050 mm

## Omrörare

Kraft (kW): 7,50  
Typ av omrörare: propeller agitator

## Tjocklek på ytterbeklädnad och isolering

Isolering mantel: Ja  
Isoleringsmaterial: Rockwool

## Mer

Isoleringstjocklek OW: 60  
Isolerad: Ja  
Vikt: 5.000