# 5200 liter tank i Syrafast 316



202 000 SEK /st exkl moms

**Additional information**: Chemistry; 4 support brackets, Fe; 2 heating connections cut off; some residues of previous content; manhole cover plated
**Volumetric volume (L)**: 5.200 L
**Pressure in tank**: pressure and vacuum
**Max. pressure (Bar)**: 2,60 Bar

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

**Min. pressure (Bar)**: 1 Bar

**Max. temperature (°C)**: 200 °C
**Material wet parts**: SS AISI 316 (V4A)
**Model**: vertical
**Configuration**: single jacketed with heat-exchanger
**Heat exchanger**: yes

**Insulation**: no
**Mobile tank**: no
**Total discharge**: yes
**Volume**: 160 L
**Max Overpressure**: 6 Bar

**Max onderdruk**: 1 Bar
**Max. working temperature**: 200 °C
**Type HE on the bottom**: half pipe welded onto the outside of the innertank
**Type HE on the cylinder**: half pipe welded onto the outside of the innertank
**Documents included**: no

**Technical drawing included**: no
**Registration plate on the tank**: yes
**Flange for agitator**: no
**Position of manway**: headside
**Outlet of tank**: 100

**Agitator**: yes
**Top**: 8,30 mm
**Cylinder**: 5,90 mm
**Bottom**: 5,30 mm
**Internal diameter tank**: 1.800 mm

**Cylinder height**: 1.500 mm
**Total height of tank**: 3.900 mm

**SKU:** 407390

## Mer information

### Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Chemistry; 4 support brackets, Fe; 2 heating connections cut off; some residues of previous content;manhole cover plated; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 2,60 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 5200

### Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

**Dimensioner av tank**
Cylinderhöjd: 1.500 mm
Invändig diameter: 1.800 mm
Total höjd: 3.900 mm

**Tjocklek på tank**
Botten: 5,30 mm
Cylinder: 5,90 mm
Topp: 8,30 mm

**Mer**
Isolerad: Nej

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se