

5200 liter tank i Syrafast 316



198,000,00 kr /st exkl moms

Additional information: Chemistry; 4 support brackets, Fe; 2 heating connections cut off; some residues of previous content; manhole cover plated

Volumetric volume (L): 5.200 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2,60 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 160 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 100

Agitator: yes

Top: 8,30 mm

Cylinder: 5,90 mm

Bottom: 5,30 mm

Internal diameter tank: 1.800 mm

Cylinder height: 1.500 mm

Total height of tank: 3.900 mm

SKU: 283345

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; 4 support brackets, Fe; 2 heating connections cut off; some residues of previous content; manhole cover plated; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2,60 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5200

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.500 mm

Invändig diameter: 1.800 mm

Total höjd: 3.900 mm

Tjocklek på tank

Botten: 5,30 mm

Cylinder: 5,90 mm

Topp: 8,30 mm

Mer

Isolerad: Nej