

52000 liter tank i GAP/Plast



180 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type MP-SEF

Additional information: lid for manway in stainless-steel (SS); set of anchorage points in stainless-steel (SS) included; tank will be delivered with Food grade certificate

Volumetric volume (L): 52.000 L

Max. density P (kg/m³): 1.300

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 60 °C



Min. temperature (°C): -10 °C

Material wet parts: polyester (fiberglass)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: flat

Total discharge: no

Fixation points: attachment points

Outer jacket (ornamental wall): polyester

Valve: aluminium

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Height manhole 1 (mm): 320 mm x H 435 mm

CIP spray ball: no

Outlet type: Guillement 2"

Total outlet valve: yes

Agitator: no

Outer diameter tank: 3.000 mm

Total height of tank: 7.895 mm

Empty weight tank: 1.400

SKU: 374786

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: GAP/Plast

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 60 °C

Maximal densitet för produkten: 1300

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: lid for manway in stainless-steel (SS); set of anchorage points in stainless-steel (SS) included; tank will be delivered with Food grade certificate

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Nej

Typ av botten: flat

Uppvärmning/kylning: Nej

Vätskeberörd yta: polyester (fiberglass)

Volym i liter: 52000

Utrustning

Fläns för omrörare: Nej

Märkskylt: Ja

Livsmedelsklassad: Ja

Teknisk ritning finns: Ja

Utloppstyp: Guillement 2"

Utloppsventil: Ja



Översikt material

Material: GAP/Plast

Fixeringspunkt(er): RVS 304

Ytterbeklädnad: polyester

Dimensioner av tank

Total höjd: 7.895 mm

Ytterdiameter: 3.000 mm

Mer

Isolerad: Nej

Vikt: 1.400