

5236 liter tank i Syrafast 316



233,000,00 kr /st exkl moms

Volumetric volume (L): 5.236 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 120 °C

Material wet parts: SS AISI 316 (V4A)



Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 22 L

Max Overpressure: 3 Bar

Max. working temperature: 120 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: headside

Outlet of tank: DN50 DIN 11851

Top: 2,50 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 1.990 mm

Outer diameter tank: 2.200 mm

Cylinder height: 1.500 mm

Total height of tank: 2.770 mm

Empty weight tank: 1.040

SKU: 419306

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 120 °C

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5236

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.500 mm

Invändig diameter: 1.990 mm

Total höjd: 2.770 mm

Ytterdiameter: 2.200 mm

Tjocklek på tank

Botten: 3 mm

Cylinder: 3 mm

Topp: 2,50 mm

Mer

Isolerad: Ja

Vikt: 1.040