525 liter tank i Syrafast 316



48 000 SEK /st exkl moms

Volumetric volume (L): 525 L
Pressure in tank: ATM - atmosferic
Min. pressure (Bar): 6 Bar
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Max. working temperature: 50 °C
Heat exchanger: RVS 304
Fixation point(s): plastic
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: yes
Position of manway: headside
Outlet of tank: DN50 DIN 11851
Internal diameter tank: 820 mm

Cylinder height: 885 mm
Total height of tank: 1.420 mm
Empty weight tank: 220

SKU: 392318

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Omrörare: Nej
Total urtappning: Ja
Undertryck (vakuum): 6 Bar
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 525

Utrustning

Dokument finns: Nej
Fläns för omrörare: Ja
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): plastic

Dimensioner av tank

Cylinderhöjd: 885 mm
Invändig diameter: 820 mm
Total höjd: 1.420 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej
Vikt: 220