

## 5250 liter tank i Syrafast 316



**58 000 SEK /st exkl moms**

**Additional information:** Chemistry; Cone height approx. 950 mm; 4 feet, Fe screwed to 4 support brackets, Fe; manhole was converted by the previous operator for his purposes; 2 rectangular sheets were welded into the cone bottom (see photos)

**Volumetric volume (L):** 5.250 L

**Pressure in tank:** ATM - atmosferic  
**Material wet parts:** SS AISI 316 (V4A)  
**Model:** vertical

**Configuration:** single-skin  
**Heat exchanger:** no  
**Insulation:** no  
**Mobile tank:** no  
**Total discharge:** yes

**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** yes  
**Flange for agitator:** no  
**Position of manway:** in the bottom

**Outlet of tank:** 50  
**Agitator:** yes  
**Power:** 6,80  
**Internal diameter tank:** 1.800 mm  
**Cylinder height:** 1.250 mm

**Total height of tank:** 4.600 mm

**SKU:** 314834

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Chemistry; Cone height approx. 950 mm; 4 feet, Fe screwed to 4 support brackets, Fe; manhole was converted by the previous operator for his purposes; 2 rectangular sheets were welded into the cone

Övrig information2: bottom (see photos); we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5250

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.250 mm

Invändig diameter: 1.800 mm

Total höjd: 4.600 mm

## Omrörare

Kraft (kW): 6,80

**Mer**

Isolerad: Nej

---