

## 530 liter tank i Syrafast 316



**166,000,00 kr /st exkl moms**

**Additional information:** Pharmacy; Original drawing available; tank was rebuilt in 1997 (e.g. changing the feet or connections); Evidence of the subsequent pressure test available; Conversion drawing only available as a fax; 1 dip tube inside the tank; some residues of previous content

**Volumetric volume (L):** 530 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 143 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 70 L

**Max Overpressure:** 3 Bar

**Max. working temperature:** 143 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** DN80 DIN 11851

**Agitator:** yes

**Number of revolutions:** 670

**Power:** 0,55

**Cylinder:** 5 mm

**Bottom:** 5 mm

**Internal diameter tank:** 800 mm

**Outer diameter tank:** 900 mm

**Cylinder height:** 900 mm

**Total height of tank:** 2.250 mm

**SKU:** 313667

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 143 °C

Mobil tank: Nej

Övrig information: Pharmacy; Original drawing available; tank was rebuilt in 1997 (e.g. changing the feet or connections); Evidence of the subsequent pressure test available; Conversion drawing only available as a

Övrig information2: fax; 1 dip tube inside the tank; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 530

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 900 mm

Invändig diameter: 800 mm

Total höjd: 2.250 mm

Ytterdiameter: 900 mm

## Omrörare

Kraft (kW): 0,55

Varvtal: 670

## Tjocklek på tank

Botten: 5 mm

Cylinder: 5 mm

## Mer

Isolerad: Ja