5300 liter tank i Rostfritt 304



106 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K-HL
Volumetric volume (L): 5.300 L
Max. density P (kg/m³): 1.150
Pressure in tank: pressure
Max. temperature (°C): 100 °C

Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: single jacketed with heat-exchanger

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Heat exchanger: yes
Insulation: no

Mobile tank: no
Top type: conical 18 °
Shape of tank: cylindrical
Bottom type: conical 18 °
Total discharge: yes

Fixation points: 4 adjustable feet
Legs: Set of baseplates and adjusting pieces included
Type of HE on the cylinder: half pipe welded onto the outside of the innertank
Position HE: the middle part of the cilinder
Number of windings: 5

Height HE: 1.061 mm
Number of sections: 1
Water pressure HE: 2,50 Bar
Steam pressure HE: 2,50 Bar
Contact surface cylinder: 3 m²

Type HE: half pipe welded onto the outside of the innertank
Heat exchanger: RVS 304
Manway(s): RVS 304
Gasket manway(s): parra rubber
Valve: RVS 316L

Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes

Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 500 mm
Hinged lid: yes

CIP spray ball: no

Tank outlet: inside Ø 65 mm
Outlet type: DIN11851 male
Total outlet valve: no, optional
Adjustable legs: yes

Agitator: no, optional
Top: 1,50 mm
Cylinder: 2 mm
Bottom: 2 mm
Internal diameter tank: 1.592 mm

Distance from outlet to ground: 230 mm
Outer diameter tank: 1.622 mm
Cylinder height: 2.500 mm
Feet height: 570 mm
Total height of tank: 3.500 mm

Empty weight tank: 350

SKU: 374825

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: pressure
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 100 °C
Maximal densitet för produkten: 1150
Mobil tank: Nej
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical 18 °
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 5300

Utrustning

Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 65 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851 male

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 2.500 mm
Höjd på fötter: 570 mm
Invändig diameter: 1.592 mm
Mått utlopp till marken: 230 mm
Total höjd: 3.500 mm
Ytterdiameter: 1.622 mm

Värmeväxlare

Ångtryck värmeväxlare: 2,50 Bar
Höjd värmeväxlare: 1.061 mm
Kontaktyta cylinder: 3 m²
Position värmeväxlare: the middle part of the cilinder
Typ av värmeväxlare på cylinder: half pipe welded onto the outside of the innertank
Vattentryck värmeväxlare: 2,50 Bar

Tjocklek på tank

Botten: 2 mm
Cylinder: 2 mm
Topp: 1,50 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej
Vikt: 350