

53000 liter tank i Syrafast 316



393 000 SEK /st exkl moms

Additional information: Contrary to the drawing, the tank stands on feet rather than on a base frame; 1 guardrail is included (the total height listed includes the guardrail); manhole approx. 500 x 400 mm; wall thickness of the lower two cylinder segments: 4 mm

Volumetric volume (L): 53.000 L



Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder

Outlet of tank: 70
Agitator: yes
Cylinder: 3 mm
Internal diameter tank: 3.500 mm
Cylinder height: 5.250 mm

Total height of tank: 8.100 mm

SKU: 706624

Mer information



Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Contrary to the drawing, the tank stands on feet rather than on a base frame; 1 guardrail is included (the total height listed includes the guardrail); manhole approx. 500 x 400 mm; wall thickness

Övrig information2: of the lower two cylinder segments: 4 mm; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 53000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 5.250 mm

Invändig diameter: 3.500 mm

Total höjd: 8.100 mm

Tjocklek på tank

Cylinder: 3 mm



Mer

Isolerad: Nej