536 liter tank i Syrafast 316



52 000 SEK /st exkl moms

Additional information: Manhole DN 450; outlet flange DN 15; crane lugs cut off
Volumetric volume (L): 536 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder
Outlet of tank: available
Cylinder: 5 mm

Bottom: 5 mm
Internal diameter tank: 800 mm
Cylinder height: 850 mm
Total height of tank: 2.020 mm

SKU: 570170

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 130 °C
Mobil tank: Nej
Övrig information: Pharmacy; Manhole DN 450; outlet flange DN 15; crane lugs cut off
Omrörare: Nej
Övertryck: 6 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 536

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 850 mm
Invändig diameter: 800 mm
Total höjd: 2.020 mm

Tjocklek på tank
Botten: 5 mm
Cylinder: 5 mm

Mer
Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se