# 53700 liter tank i Syrafast 316



546 000 SEK /st exkl moms

**Additional information**: Yeast; Manhole approx. 510 x 410 mm; half-pipe coils in the lower cylinder section and bottom panel (2 separate circuits, see drawing); Tank feet are included separately; the weld seam of the insulation jacket has come loose in one spot on the upper bottom (see photos)
**Volumetric volume (L)**: 53.700 L
**Pressure in tank**: pressure

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

**Max. temperature (°C)**: 110 °C
**Material wet parts**: SS AISI 316 (V4A)

**Model**: vertical
**Configuration**: insulated
**Heat exchanger**: no
**Insulation**: yes
**Mobile tank**: no

**Total discharge**: yes
**Volume**: 16 L
**Max Overpressure**: 4 Bar
**Max. working temperature**: 110 °C
**Documents included**: no

**Technical drawing included**: no
**Registration plate on the tank**: yes
**Flange for agitator**: no
**Outlet of tank**: 108
**Agitator**: yes

**Number of revolutions**: 358
**Power**: 4
**Top**: 4 mm
**Cylinder**: 4 mm
**Bottom**: 5 mm

**Internal diameter tank**: 3.240 mm
**Outer diameter tank**: 3.412 mm
**Cylinder height**: 5.850 mm
**Total height of tank**: 9.800 mm

**SKU:** 703364

# Mer information

**Beskrivning av produkt**

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Max. arbetstemperatur: 110 °C
Mobil tank: Nej
Övrig information: Food; Manhole diameter: approx. 510 x 410 mm; dimensions as shown in the drawing; solid-tube coils in the lower cylinder section and at the bottom are suitable for cooling only (2 separate circuits;
Övrig information2: see drawing); we can’t give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 53700

**Utrustning**

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

**Översikt material**

Material: Syrafast 316

**Dimensioner av tank**
Cylinderhöjd: 5.850 mm
Invändig diameter: 3.240 mm
Total höjd: 9.414 mm
Ytterdiameter: 3.412 mm

**Omrörare**
Kraft (kW): 4
Varvtal: 358

**Tjocklek på tank**
Botten: 5 mm
Cylinder: 4 mm
Topp: 4 mm

**Mer**
Isolerad: Ja