

540 liter tank i Syrafast 316



42,000,00 kr /st exkl moms

Additional information: plastics industry; a number of connections were changed by the former operator; 1 overflow pipe inside; mounting of the manhole cover incomplete; 1 smaller dent inside the tank; some residues of previous content; dents at the insulation jacket

Volumetric volume (L): 540 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 32 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 130 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN50

Internal diameter tank: 690 mm

Outer diameter tank: 850 mm

Cylinder height: 1.200 mm

Total height of tank: 2.400 mm

SKU: 266836

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: plastics industry; a number of connections were changed by the former operator; 1 overflow pipe inside; mounting of the manhole cover incomplete; 1 smaller dent inside the tank; some residues of

Övrig information2: previous content;dents at the insulation jacket; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 540

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.200 mm

Invändig diameter: 690 mm

Total höjd: 2.400 mm

Ytterdiameter: 850 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Ja