

## 5400 liter tank i Syrafast 316



**141,000,00 kr /st exkl moms**

**Additional information:** Chemistry; Support ring, Fe; Half-coil not included in vessel drawing; some residues of previous content

**Volumetric volume (L):** 5.400 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 6 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** flange DN100

**Agitator:** yes

**Number of revolutions:** 450

**Power:** 3,60

**Top:** 16 mm

**Cylinder:** 6 mm

**Bottom:** 8 mm

**Internal diameter tank:** 1.800 mm

**Cylinder height:** 1.690 mm

**Total height of tank:** 3.700 mm

**SKU:** 276979

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Support ring, Fe; Half-coil not included in vessel drawing ; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5400

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

## **Dimensioner av tank**

Cylinderhöjd: 1.690 mm  
Invändig diameter: 1.800 mm  
Total höjd: 3.700 mm

## **Omrörare**

Kraft (kW): 3,60  
Varvtal: 450

## **Tjocklek på tank**

Botten: 8 mm  
Cylinder: 6 mm  
Topp: 16 mm

## **Mer**

Isolerad: Nej