5400 liter tank i Syrafast 316



140 000 SEK /st exkl moms

Additional information: Support ring, Fe; Half-coil not included in vessel drawing; some residues of previous content
Volumetric volume (L): 5.400 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: flange DN100
Agitator: yes
Number of revolutions: 450
Power: 3,60
Top: 16 mm

Cylinder: 6 mm
Bottom: 8 mm
Internal diameter tank: 1.800 mm
Cylinder height: 1.690 mm
Total height of tank: 3.700 mm

SKU: 401027

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Chemistry; Support ring, Fe; Half-coil not included in vessel drawing ; some residues of previous content; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 6 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 5400

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.690 mm
Invändig diameter: 1.800 mm
Total höjd: 3.700 mm

Omrörare
Kraft (kW): 3,60
Varvtal: 450

Tjocklek på tank
Botten: 8 mm
Cylinder: 6 mm
Topp: 16 mm

Mer
Isolerad: Nej