

5450 liter tank i Syrafast 316



115 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; 1 manhole DN 500 each in the upper bottom and in the cylinder; 1 flanged taper on the outlet flange; manhole cover plated

Volumetric volume (L): 5.480 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 3,20 Bar

Max onderdruk: 1 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN80

Top: 6,16 mm

Cylinder: 6 mm

Bottom: 5,20 mm

Internal diameter tank: 1.800 mm

Cylinder height: 1.660 mm

Total height of tank: 3.550 mm

Empty weight tank: 850

SKU: 283306

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; 1 manhole DN 500 each in the upper bottom and in the cylinder; 1 flanged taper on the outlet flange ; manhole cover plated

Omrörare: Nej

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5480

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.660 mm

Invändig diameter: 1.800 mm

Total höjd: 3.550 mm

Tjocklek på tank

Botten: 5,20 mm

Cylinder: 6 mm

Topp: 6,16 mm

Mer

Isolerad: Nej

Vikt: 850