

5462 liter tank i Syrafast 316



64,000,00 kr /st exkl moms

Additional information: lukewarm water; manhole diameter: approx. 500 mm; Slight metallic discoloration inside the tank; some residues of previous content

Volumetric volume (L): 5.462 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 45 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 80

Internal diameter tank: 1.494 mm

Outer diameter tank: 1.600 mm

Cylinder height: 2.920 mm

Total height of tank: 4.120 mm

Total outer width: 2.000 mm

SKU: 302506

Mer information



Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated

Max. arbetstemperatur: 45 °C

Mobil tank: Nej

Övrig information: lukewarm water; manhole diameter: approx. 500 mm; Slight metallic discoloration inside the tank; some residues of previous content

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5462

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.920 mm

Invändig diameter: 1.494 mm

Total höjd: 4.120 mm

Ytterdiameter: 1.600 mm

Mer

Isolerad: Ja

