550 liter tank i Syrafast 316



106 000 SEK /st exkl moms

Volumetric volume (L): 550 L
Pressure in tank: pressure
Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 135 °C

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

Mobile tank: no
Total discharge: yes
Volume: 67 L
Max Overpressure: 2 Bar
Max. working temperature: 135 °C

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: DN40 DIN 11851
Agitator: yes
Internal diameter tank: 650 mm
Outer diameter tank: 890 mm

Total height of tank: 2.300 mm

SKU: 440381

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 135 °C
Mobil tank: Nej
Övrig information: pharmacy; we can’t give any guarantees about the heating/cooling jacket; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 3 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 550

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 650 mm
Total höjd: 2.300 mm
Ytterdiameter: 890 mm

Mer
Isolerad: Ja