

5500 liter tank i Rostfritt 304



59,000,00 kr /st exkl moms

Article type: second-hand storage tank

Additional information: The agitator drive is missing, the insulation sheathing has come loose here and there

Volumetric volume (L): 5.500 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no



Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 3 non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): aluminium

Manway(s): RVS 304

Gasket manway(s): unknown

Valve: RVS 304

Gasket shut-off valve (mat): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Tank outlet: inside Ø 40 mm

Total outlet valve: yes

Internal diameter tank: 1.450 mm

Distance from outlet to ground: 300 mm

Outer diameter tank: 1.580 mm

Cylinder height: 3.350 mm

Total height of tank: 4.400 mm

Empty weight tank: 600

SKU: 489669

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: The agitator drive is missing, the insulation sheathing has come loose here and there

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Nej

Utloppsventil: Ja

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Isoleringsmaterial: Rockwool

Ytterbeklädnad: aluminium

Dimensioner av tank

Cylinderhöjd: 3.350 mm

Invändig diameter: 1.450 mm

Mått utlopp till marken: 300 mm

Total höjd: 4.400 mm

Ytterdiameter: 1.580 mm

Tjocklek på ytterbeklädnad och isolering

Isoleringsmaterial: Rockwool

Mer

Isolerad: Ja

Vikt: 600