

## 5500 liter tank i Syrafast 316



**167 000 SEK /st exkl moms**

**Additional information:** Biogas plant; foot ends have been cut off and are loose (see photos); diameter manhole 450 mm; flanged fitting at the outlet; metallic discolourations inside; some residues of previous content

**Volumetric volume (L):** 5.500 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 4 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 200 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Heat exchanger:** RVS 316

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** flange DN100

**Agitator:** yes

**Number of revolutions:** 49 / 98

**Power:** 5 / 7.5

**Cylinder:** 8 mm

**Bottom:** 10 mm

**Internal diameter tank:** 1.800 mm

**Cylinder height:** 1.570 mm

**Total height of tank:** 4.500 mm

SKU: 272176

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Biogas plant; foot ends have been cut off and are loose (see photos); diameter manhole 450 mm; flanged fitting at the outlet; metallic discolourations inside ; some residues of previous content; we

Övrig information2: can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5500

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.570 mm

Invändig diameter: 1.800 mm

Total höjd: 4.500 mm

## Omrörare

Kraft (kW): 5 / 7.5

Varvtal: 49 / 98

## Tjocklek på tank

Botten: 10 mm

Cylinder: 8 mm

## Mer

Värmeväxlare: RVS 316

Isolerad: Nej