

5500 liter tank i Syrafast 316



170,000,00 kr /st exkl moms

Additional information: Biogas plant; foot ends have been cut off and are loose (see photos); diameter manhole 450 mm; flanged fitting at the outlet; metallic discolourations inside; some residues of previous content

Volumetric volume (L): 5.500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 200 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 316

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN100

Agitator: yes

Number of revolutions: 49 / 98

Power: 5 / 7.5

Cylinder: 8 mm

Bottom: 10 mm

Internal diameter tank: 1.800 mm

Cylinder height: 1.570 mm

Total height of tank: 4.500 mm

SKU: 272176

Mer information
