

5500 liter tank i Syrafast 316



278,000,00 kr /st exkl moms

Additional information: Saline solution; Dents in the insulation jacket possible; The production and documentation drawings are available from the manufacturer and can be purchased separately from there; some residues of previous content; pipe end cut flush

Volumetric volume (L): 5.500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 154 L

Max Overpressure: 2,50 Bar

Max onderdruk: 1 Bar

Max. working temperature: 140 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 38

Agitator: yes

Number of revolutions: 429

Power: 2,20

Internal diameter tank: 1.680 mm

Outer diameter tank: 1.890 mm

Total height of tank: 3.500 mm

SKU: 278833

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 140 °C

Mobil tank: Nej

Övrig information: Saline solution; Dents in the insulation jacket possible; The production and documentation drawings are available from the manufacturer and can be purchased separately from there ; some residues of

Övrig information2: previous content; pipe end cut flush; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.680 mm

Total höjd: 3.500 mm

Ytterdiameter: 1.890 mm

Omrörare

Kraft (kW): 2,20

Varvtal: 429

Mer

Värmeväxlare: RVS 304

Isolerad: Ja