

## 5530 liter tank i Rostfritt 304



**156,000,00 kr /st exkl moms**

**Additional information:** Dairy; Double jacket probably with trickle ring - only suitable for pressureless tempering; the welding of the double jacket in the upper area has come loose slightly in places; outlet diameter 65 mm (tapers towards the tank to approx. 50 mm); small dents inside the tank; heating connections cut off; pipe end cut flush

**Volumetric volume (L):** 5.530 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 145 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 15.5 / 31

**Power:** 0.8 / 1.6

**Internal diameter tank:** 1.550 mm

**Outer diameter tank:** 1.660 mm

**Cylinder height:** 2.500 mm

**Total height of tank:** 4.350 mm

**SKU:** 443435

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 145 °C

Mobil tank: Nej

Övrig information: Dairy; Double jacket probably with trickle ring – only suitable for pressureless tempering; the welding of the double jacket in the upper area has come loose slightly in places; outlet diameter 65

Övrig information2: mm (tapers towards the tank to approx. 50 mm); small dents inside the tank; heating connections cut off; pipe end cut flush; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5530

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

## **Dimensioner av tank**

Cylinderhöjd: 2.500 mm  
Invändig diameter: 1.550 mm  
Total höjd: 4.350 mm  
Ytterdiameter: 1.660 mm

## **Omrörare**

Kraft (kW): 0.8 / 1.6  
Varvtal: 15.5 / 31

## **Mer**

Isolerad: Nej