55610 liter tank i Syrafast 316



401 000 SEK /st exkl moms

Additional information: Solvents
Volumetric volume (L): 55.610 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 1 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,25 Bar

Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: flange DN100
Agitator: yes

Number of revolutions: 90
Power: 10
Top: 10 mm
Cylinder: 6 mm
Bottom: 12 mm

Internal diameter tank: 3.300 mm
Cylinder height: 5.590 mm
Total height of tank: 8.600 mm

SKU: 476626

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Solvents; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 1 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,25 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 55610

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 5.590 mm
Invändig diameter: 3.300 mm
Total höjd: 8.600 mm

Omrörare
Kraft (kW): 10
Varvtal: 90

Tjocklek på tank
Botten: 12 mm
Cylinder: 6 mm
Topp: 10 mm

Mer
Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se