5570 liter tank i Syrafast 316



265 000 SEK /st exkl moms

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Article type: second-hand pressure tank
Additional information: Total height legs inclusive but without gear motor is 5250mm ; Gear motor present, though without shaft and propellor.; we can't give any guarantees about the heating/cooling jacket
Volumetric volume (L): 5.570 L
Ra inner weld: 0,80
Pressure in tank: pressure and vacuum

Design pressure (Bar): 0 Bar
Max. pressure (Bar): 4 Bar
Min. pressure (Bar): 0 Bar
Max. temperature (°C): 152 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Top type: dished
Shape of tank: cylindrical
Bottom type: dished
Wall type: flat
Bottom outlet: yes

Total discharge: yes
Fixation points: 3 non adjustable feet
Type of HE on the cylinder: dimple-jacket
Position HE: the complet cilinder
Water pressure HE: 4,50 Bar

Steam pressure HE: 4 Bar
Hydraulic test pressure: 5,90 Bar
Working temperature HE cylinder: 152 °C
Heat exchanger: RVS 304
Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 316
Gasket manway(s): unknown
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: at the top
Agitator: no, optional

Outer diameter tank: 1.500 mm

SKU: 418625

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Designtryck för tanken: 0 Bar
Konfiguration: isolert med varmeveksler
Max. arbetstemperatur: 152 °C
Mobil tank: Nej
Övrig information: Total height legs inclusive but without gear motor is 5250mm ; Gear motor present, though without shaft and propellor.; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 4 Bar
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: dished
Undertryck (vakuum): 0 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 5570

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316
Fixeringspunkt(er): RVS 304
Ytterbeklädnad: RVS 304

Dimensioner av tank
Ytterdiameter: 1.500 mm

Värmeväxlare
Ångtryck värmeväxlare: 4 Bar
Arbetstemperatur värmeväxlare cylinder: 152 °C
Hydrauliskt provtryck botten: 5,90 Bar
Hydrauliskt provtryck: 5,90 Bar
Position värmeväxlare: the complet cilinder
Typ av värmeväxlare på cylinder: dimple-jacket
Vattentryck värmeväxlare: 4,50 Bar

Mer
Värmeväxlare: RVS 304
Isolerad: Ja

Rodervägen 57
891 78 Bonässund
info@processoverskott.se