

560 liter tank i Syrafast 316



36,000,00 kr /st exkl moms

Additional information: adhesive production; some residues of previous content

Volumetric volume (L): 560 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: open

Total discharge: yes

Volume: 15 L

Max Overpressure: 10 Bar

Max. working temperature: 150 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 32

Agitator: yes

Number of revolutions: 690

Power: 0,95

Internal diameter tank: 790 mm

Outer diameter tank: 900 mm

Cylinder height: 1.000 mm

Total height of tank: 2.400 mm

SKU: 270118

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: adhesive production; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 560

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.000 mm

Invändig diameter: 790 mm

Total höjd: 2.400 mm

Ytterdiameter: 900 mm

Omrörare

Kraft (kW): 0,95

Varvtal: 690

Mer

Värmeväxlare: RVS 304

Isolerad: Ja