560 liter tank i Syrafast 316

31 000 SEK /st exkl moms

Additional information: adhesive production; some residues of previous content
Volumetric volume (L): 560 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 150 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Top type: open
Total discharge: yes
Volume: 15 L
Max Overpressure: 10 Bar
Max. working temperature: 150 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 32
Agitator: yes
Number of revolutions: 690

Power: 0,95
Internal diameter tank: 790 mm
Outer diameter tank: 900 mm
Cylinder height: 1.000 mm
Total height of tank: 2.400 mm

SKU: 394259

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: adhesive production; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 560

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.000 mm
Invändig diameter: 790 mm
Total höjd: 2.400 mm
Ytterdiameter: 900 mm

Omrörare
Kraft (kW): 0,95
Varvtal: 690

Mer
Värmeväxlare: RVS 304
Isolerad: Ja