# 560 liter tank i Syrafast 316



31 000 SEK /st exkl moms

**Additional information**: adhesive production; Loose lid with hinged segment; some residues of previous content; bump at the insulation jacket
**Volumetric volume (L)**: 560 L
**Pressure in tank**: pressure
**Max. temperature (°C)**: 150 °C

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

**Material wet parts**: SS AISI 316 (V4A)

**Model**: vertical
**Configuration**: insulated
**Heat exchanger**: no
**Insulation**: yes
**Mobile tank**: no

**Total discharge**: yes
**Volume**: 20 L
**Max Overpressure**: 10 Bar
**Max. working temperature**: 150 °C
**Type HE on the bottom**: half pipe welded onto the outside of the innertank

**Type HE on the cylinder**: half pipe welded onto the outside of the innertank
**Heat exchanger**: RVS 316
**Documents included**: no
**Technical drawing included**: no
**Registration plate on the tank**: yes

**Flange for agitator**: no
**Outlet of tank**: flange DN32
**Agitator**: yes
**Number of revolutions**: 695
**Power**: 0,95

**Cylinder**: 2,50 mm
**Bottom**: 2,50 mm
**Internal diameter tank**: 800 mm
**Outer diameter tank**: 900 mm
**Cylinder height**: 1.010 mm

**Total height of tank**: 2.600 mm

**SKU:** 393884

# Mer information

**Beskrivning av produkt**

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: adhesive production; loose lid with folding flap segment; some residues of previous content;bump at the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't
Övrig information2: give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 560

**Utrustning**

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

**Översikt material**

Material: Syrafast 316

**Dimensioner av tank**
Cylinderhöjd: 1.010 mm
Invändig diameter: 800 mm
Total höjd: 2.600 mm
Ytterdiameter: 900 mm

**Omrörare**
Kraft (kW): 0,95
Varvtal: 695

**Tjocklek på tank**
Botten: 2,50 mm
Cylinder: 2,50 mm

**Mer**
Värmeväxlare: RVS 304
Isolerad: Ja