

5600 liter tank i Rostfritt 304



236 000 SEK /st exkl moms

Additional information: Cosmetics; Flanged to the outlet 1 reduction to diameter 65 mm; 1 immersion pipe inside the vessel; 1 pallet with accessories (foot pedestals, fittings etc.) is included in the scope of delivery; these accessories have not been taken into account in the total height stated

Volumetric volume (L): 5.600 L

Pressure in tank: vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 250 L
Max Overpressure: 3 Bar

Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: yes
Position of manway: headside
Outlet of tank: 100

Internal diameter tank: 1.880 mm
Outer diameter tank: 2.050 mm
Cylinder height: 1.500 mm
Total height of tank: 3.000 mm

SKU: 310034

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Cosmetics; Flanged to the outlet 1 reduction to diameter 65 mm; 1 dip tube inside the tank; 1 pallet with accessories (foot platforms, fittings, etc.) is included in the scope of delivery; these

Övrig information2: accessories were not taken into account in the stated total height; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5600

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.500 mm
Invändig diameter: 1.880 mm
Total höjd: 3.000 mm
Ytterdiameter: 2.050 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Ja