

## 5650 liter tank i Syrafast 316



**174 000 SEK /st exkl moms**

**Additional information:** Pharmaceutical Chemistry; Claws made of Fe; insulating jacket has partially detached in the area of the lower base (see photos)

**Volumetric volume (L):** 5.650 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 166 L

**Max Overpressure:** 6 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 140

**Agitator:** yes

**Number of revolutions:** 55,80

**Power:** 2

**Internal diameter tank:** 1.800 mm

**Outer diameter tank:** 2.100 mm

**Total height of tank:** 3.750 mm

**SKU:** 487175

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical Chemistry; Support brackets, Fe; insulation jacket has partially come loose in the area of the lower bottom (see photos); we can't give any guarantees about the heating/cooling

Övrig information2: jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5650

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Invändig diameter: 1.800 mm

Total höjd: 3.750 mm

Ytterdiameter: 2.100 mm

## Omrörare

Kraft (kW): 2

Varvtal: 55,80

## Mer

Isolerad: Ja