5650 liter tank i Syrafast 316

173,000,00 kr /st exkl moms

Additional information: Pharmaceutical Chemistry; Support brackets, Fe; insulation jacket has partially come loose in the area of the lower bottom (see photos)
Volumetric volume (L): 5.650 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Max. pressure (Bar): 3,20 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 166 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 140

Agitator: yes
Number of revolutions: 55,80
Power: 2
Internal diameter tank: 1.800 mm
Outer diameter tank: 2.100 mm

Total height of tank: 3.750 mm

SKU: 487175

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmaceutical Chemistry; Support brackets, Fe; insulation jacket has partially come loose in the area of the lower bottom (see photos); we can't give any guarantees about the heating/cooling
Övrig information2: jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 5650

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Dimensioner av tank
Invändig diameter: 1.800 mm
Total höjd: 3.750 mm
Ytterdiameter: 2.100 mm

Omrörare
Kraft (kW): 2
Varvtal: 55,80

Mer
Isolerad: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor