

5650 liter tank i Syrafast 316



214,000,00 kr /st exkl moms

Additional information: Water for injections in pharmacy; Manhole DN 500; Feet were shared from the previous operator to allow the tank to be placed in a lower space

Volumetric volume (L): 5.650 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 144 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: flange DN80

Cylinder: 5,80 mm

Bottom: 5,80 mm

Internal diameter tank: 1.800 mm

Outer diameter tank: 1.900 mm

Cylinder height: 1.750 mm

Total height of tank: 3.700 mm

SKU: 290945

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated

Max. arbetstemperatur: 144 °C

Mobil tank: Nej

Övrig information: Water for injections in pharmacy; Manhole DN 500; Feet were shared from the previous operator to allow the tank to be placed in a lower space

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5650

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.750 mm

Invändig diameter: 1.800 mm

Total höjd: 3.700 mm

Ytterdiameter: 1.900 mm

Tjocklek på tank

Botten: 5,80 mm

Cylinder: 5,80 mm

Mer

Isolerad: Ja