

## 5650 liter tank i Syrafast 316



**214,000,00 kr /st exkl moms**

**Additional information:** Water for injections in pharmacy; Manhole DN 500; Feet were shared from the previous operator to allow the tank to be placed in a lower space

**Volumetric volume (L):** 5.650 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 144 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** cylinder

**Outlet of tank:** flange DN80

**Cylinder:** 5,80 mm

**Bottom:** 5,80 mm

**Internal diameter tank:** 1.800 mm

**Outer diameter tank:** 1.900 mm

**Cylinder height:** 1.750 mm

**Total height of tank:** 3.700 mm

**SKU:** 290945

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated

Max. arbetstemperatur: 144 °C

Mobil tank: Nej

Övrig information: Water for injections in pharmacy; Manhole DN 500; Feet were shared from the previous operator to allow the tank to be placed in a lower space

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5650

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.750 mm

Invändig diameter: 1.800 mm

Total höjd: 3.700 mm

Ytterdiameter: 1.900 mm

**Tjocklek på tank**

Botten: 5,80 mm

Cylinder: 5,80 mm

**Mer**

Isolerad: Ja