# 5650 liter tank i Syrafast 316



213 000 SEK /st exkl moms

**Additional information**: Water for injections in pharmacy; Manhole DN 500; feet were split by the previous operator so that the tank could be installed in a lower room
**Volumetric volume (L)**: 5.650 L
**Pressure in tank**: pressure and vacuum
**Max. pressure (Bar)**: 3 Bar

**Min. pressure (Bar)**: 1 Bar

**Max. temperature (°C)**: 144 °C
**Material wet parts**: SS AISI 316 (V4A)
**Model**: vertical
**Configuration**: insulated
**Heat exchanger**: no

**Insulation**: yes
**Mobile tank**: no
**Total discharge**: yes
**Documents included**: no
**Technical drawing included**: no

**Registration plate on the tank**: yes
**Flange for agitator**: no
**Position of manway**: cylinder
**Outlet of tank**: flange DN80
**Cylinder**: 5,80 mm

**Bottom**: 5,80 mm
**Internal diameter tank**: 1.800 mm
**Outer diameter tank**: 1.900 mm
**Cylinder height**: 1.750 mm
**Total height of tank**: 3.700 mm

**SKU:** 414293

## Mer information

## Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated
Max. arbetstemperatur: 144 °C
Mobil tank: Nej
Övrig information: Water for injections in pharmacy; Manhole DN 500; Feet were shared from the previous operator to allow the tank to be placed in a lower space
Omrörare: Nej
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 5650

## Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.750 mm
Invändig diameter: 1.800 mm
Total höjd: 3.700 mm
Ytterdiameter: 1.900 mm

**Tjocklek på tank**
Botten: 5,80 mm
Cylinder: 5,80 mm

**Mer**
Isolerad: Ja