

568 liter tank i Syrafast 316



58 000 SEK /st exkl moms

Additional information: Stainless steel support ring; hand hole opens pneumatically; discharge fitting incomplete

Volumetric volume (L): 568 L

Pressure in tank: ATM - atmospheric



Max. temperature (°C): 90 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 60 L

Max Overpressure: 2,50 Bar

Max. working temperature: 90 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN50

Agitator: yes

Number of revolutions: 498 / 975

Power: 0.55 / 0.88

Internal diameter tank: 900 mm

Outer diameter tank: 1.160 mm

Total height of tank: 2.400 mm

SKU: 705916

Mer information



Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Max. arbetstemperatur: 90 °C

Mobil tank: Nej

Övrig information: Stainless steel support ring; hand hole opens pneumatically; discharge fitting incomplete; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 568

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 900 mm

Total höjd: 2.400 mm

Ytterdiameter: 1.160 mm

Omrörare

Kraft (kW): 0.55 / 0.88

Varvtal: 498 / 975



Mer

Isolerad: Ja