

5685 liter tank i Syrafast 316



169,000,00 kr /st exkl moms

Additional information: Remnants of the insulating jacket on the outside of the cylinder; 1 DN 100 connection in the manhole cover

Volumetric volume (L): 5.685 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 210 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: headside

Outlet of tank: 130

Internal diameter tank: 1.780 mm

Cylinder height: 1.720 mm

Total height of tank: 2.850 mm

SKU: 287048

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Remnants of the insulating jacket on the outside of the cylinder; 1 DN 100 connection in the manhole cover

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5685

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.720 mm

Invändig diameter: 1.780 mm

Total höjd: 2.850 mm

Mer

Isolerad: Nej