

## 5685 liter tank i Syrafast 316



**168 000 SEK /st exkl moms**

**Additional information:** Remnants of the insulating jacket on the outside of the cylinder; 1 DN 100 connection in the manhole cover

**Volumetric volume (L):** 5.685 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 6 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 210 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** yes

**Position of manway:** headside

**Outlet of tank:** 130

**Internal diameter tank:** 1.780 mm

**Cylinder height:** 1.720 mm

**Total height of tank:** 2.850 mm

**SKU:** 287048

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Remnants of the insulating jacket on the outside of the cylinder; 1 DN 100 connection in the manhole cover

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5685

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

**Dimensioner av tank**

Cylinderhöjd: 1.720 mm

Invändig diameter: 1.780 mm

Total höjd: 2.850 mm

**Mer**

Isolerad: Nej