5700 liter tank i Syrafast 316



131 000 SEK /st exkl moms

Additional information: Manhole DN 600; 1 heating coil originally located inside the vessel is no longer present; Metallic discolouration inside
Volumetric volume (L): 5.700 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 40 L
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder
Outlet of tank: flange DN100

Top: 8,40 mm
Cylinder: 6 mm
Bottom: 7,80 mm
Internal diameter tank: 1.780 mm
Outer diameter tank: 2.020 mm

Cylinder height: 1.750 mm
Total height of tank: 3.650 mm

SKU: 399305

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmacy; Manhole DN 600; 1 heating coil originally located inside the vessel no longer exists ; Metallic discolouration inside
Omrörare: Nej
Övertryck: 6 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 5700

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.750 mm
Invändig diameter: 1.780 mm
Total höjd: 3.650 mm
Ytterdiameter: 2.020 mm

Tjocklek på tank
Botten: 7,80 mm
Cylinder: 6 mm
Topp: 8,40 mm

Mer
Isolerad: Ja