

5700 liter tank i Syrafast 316



130,000,00 kr /st exkl moms

Additional information: Pharmacy; Manhole DN 600; 1 heating coil originally located inside the vessel no longer exists; Metallic discolouration inside

Volumetric volume (L): 5.700 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 40 L

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: flange DN100

Top: 8,40 mm

Cylinder: 6 mm

Bottom: 7,80 mm

Internal diameter tank: 1.780 mm

Outer diameter tank: 2.020 mm

Cylinder height: 1.750 mm

Total height of tank: 3.650 mm

SKU: 275224

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmacy; Manhole DN 600; 1 heating coil originally located inside the vessel no longer exists ; Metallic discolouration inside

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5700

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.750 mm

Invändig diameter: 1.780 mm

Total höjd: 3.650 mm

Ytterdiameter: 2.020 mm

Tjocklek på tank

Botten: 7,80 mm

Cylinder: 6 mm

Topp: 8,40 mm

Mer

Isolerad: Ja