

5750 liter tank i Syrafast 316



139 000 SEK /st exkl moms

Additional information: Some flanges are made of Fe; some residues of previous content; manhole cover plated; Metallic discolouration inside

Volumetric volume (L): 5.750 L

Pressure in tank: vacuum



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 250 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 150 L

Max Overpressure: 3,20 Bar

Max onderdruk: 1 Bar

Max. working temperature: 250 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN80

Top: 15 mm

Cylinder: 9 mm

Bottom: 9 mm

Internal diameter tank: 1.800 mm

Cylinder height: 1.720 mm

Total height of tank: 3.100 mm

SKU: 707773



Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 250 °C

Mobil tank: Nej

Övrig information: Some flanges are made of Fe; some residues of previous content;manhole cover plated;Metallic discolouration inside

Omrörare: Nej

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5750

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.720 mm

Invändig diameter: 1.800 mm

Total höjd: 3.100 mm



Tjocklek på tank

Botten: 9 mm

Cylinder: 9 mm

Topp: 15 mm

Mer

Isolerad: Nej