

## 580 liter tank i Syrafast 316



**32 000 SEK /st exkl moms**

**Additional information:** Rennet production; 3-legged frame, Aisi 304; 1 rectangular opening approx. 350 x 500 mm in the upper bottom (lid suspension incomplete); 1 rectangular stainless steel sheet welded into the lower bottom (see photos); some residues of previous content

**Volumetric volume (L):** 580 L

**Pressure in tank:** ATM - atmosferic  
**Material wet parts:** SS AISI 316 (V4A)  
**Model:** vertical

**Configuration:** single-skin  
**Heat exchanger:** no  
**Insulation:** no  
**Mobile tank:** no  
**Total discharge:** yes

**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** no  
**Flange for agitator:** no  
**Outlet of tank:** DN40 DIN 11851

**Agitator:** yes  
**Number of revolutions:** 25  
**Power:** 1,10  
**Internal diameter tank:** 1.250 mm  
**Cylinder height:** 500 mm

**Total height of tank:** 1.750 mm

**SKU:** 403418

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Rennet production; 3-legged frame, Aisi 304; 1 rectangular opening approx. 350 x 500 mm in the upper bottom (lid suspension incomplete); 1 rectangular stainless steel sheet welded into the lower

Övrig information2: bottom (see photos); some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 580

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 500 mm

Invändig diameter: 1.250 mm

Total höjd: 1.750 mm

**Omrörare**

Kraft (kW): 1,10

Varvtal: 25

**Mer**

Isolerad: Nej